


TECHNICAL SPECIFICATION

MODEL:	1850PT
CAPACITY (L):	1850
LENGTH (mm):	2800
WIDTH (mm):	1400
HEIGHT (mm):	4500
WEIGHT (kg):	1050
MATERIAL:	3mm mild steel



Need more information?

Call us on:
01889 567700



SPECIFICATION

- ▶ Fire protective jacket on primary tank
- ▶ 4" BSP fill connection with cap and chain
- ▶ 2" 4.5m spark arrestor vent stack
- ▶ Lockable access hatch
- ▶ Plastic dipstick
- ▶ Fork lift skids
- ▶ Bolt down connections
- ▶ Earth strap and rod
- ▶ Powder coated paintwork. Colour RAL 7035 Grey (tank and vent) and RAL 9006 Grey (lid)
- ▶ Pump with inline strainer options: 240V, 12V, hand pump
- ▶ Steel welded construction for primary tank and bund

OPTIONAL EXTRAS

- ▶ Hand pump
- ▶ 12V pump
- ▶ 240V pump
- ▶ Flowmeter
- ▶ Pump cabinet
- ▶ Fire kit
- ▶ Spill kit
- ▶ 1.5" top suction complete with anti-siphon valve and dispenser plinth

Note: This system is not designed to be sited on a raised base, the tank must be sited at the same level as the delivery tanker.

Designed in accordance with HSG176, DSEAR and the Blue Book

